

Product: ELECTRO-ACOUSTIC TRANSDUCER Description: ROHS COMPLIANT Part Number:BRT1209P-12-C

SPECIFICATIONS:


RATED VOLTAGE:	12 VDC
OPERATING VOLTAGE:	7 ~ 15
MAX CURRENT:	30 mA
SOUND OUTPUT LEVEL:	80dB @ 10 cm
TERMINAL TYPE:	2 PINS
RESONANT FREQUENCY:	2300 Hz
OPERATING TEMPERATURE:	-20 TO +70°C
TONE MODE:	CONTINUOUS
PULSE RATE:	N/A
COIL RESISTANCE:	NOT APPLIC
COIL IMPEDANCE:	WITH BUILT
FRAME DIAMETER:	12.0 mm
FRAME DEPTH:	9.5 mm
MOUNTING DIMENSIONS:	7.6 mm

COMMENTS:

*VALUE APPLYING RATED VOLTAGE (RESONANT FREQUENCY,

**VALUE APPLYING (RESONANT FREQUENCY, SINE WAVE, M

DIMENSIONS:



Lake-View Electronics Corp. 1054 Pioneer Rd. Grafton, WI Ph: 262-377-8250 Fax: 262-375-0109 www.lvelectronics.com Email: sales@lvelectronics.com