

Heat-shrinkable terminals, splices, disconnects




Heat-shrinkable fully insulated female disconnects



Cat. no.	Pkg. qty.	Wire		Tab size (in.)	Rec. tool	Dimensions (in.)	
		range (AWG)	Max. ins. (in.)			A	
RAS18-250AX	25	22-18	0.170	0.250 x 0.032	ERG4255	1.82	
RBS14-250AX	25	16-14	0.200	0.250 x 0.032		1.77	
RCS10-250AX	25	12-10	0.250	0.250 x 0.032		1.80	

Diagram




Heat-shrinkable fully insulated male tabs



Cat. no.	Pkg. qty.	Wire		Tab size (in.)	Rec. tool	Dimensions (in.)	
		range (AWG)	Max. ins. (in.)			A	
18RAS-251TX	25	22-18	0.170	0.250 x 0.032	ERG4255	1.80	
14RBS-251TX	25	16-14	0.200	0.250 x 0.032		1.75	
10RCS-251TX	25	12-10	0.250	0.250 x 0.032		1.80	

Diagram



Heat-shrinkable butt splices



Cat. no.	Pkg. qty.	Wire		Rec. tool	Dimensions (in.)	
		range (AWG)	Max. ins. (in.)		A	B
2RAS18X	50	22-18	0.170	ERG4255	1.50	.25
RAAS22X	500	22-18	0.170		1.50	.26
2RBS14X	50	16-14	0.200		1.50	.26
RBBS22X	500	16-14	0.200		1.60	.31
2RCS10X	25	12-10	0.250		1.60	.31
RCCS22X	250	12-10	0.250		1.60	.31

Diagram



Everything you need to make fully sealed connections in one handy kit.

- Tools: (1) butane torch; (1) wire stripper; (1) ratchet crimp tool
- Butt splices: (20) #22-#18 AWG; (20) #16-#14 AWG; (15) #12-#10 AWG
- Ring terminals: (20) #16-#14 AWG #10 stud; (2) #16-#14 AWG #8 stud; (15) #12-#10 AWG 1/4" stud

Heat-shrink terminal kit with tools

Cat. no.	Description	Std. pkg. qty.
STAPOUCH-HS	Heat-shrink terminal kit with tools	1