

## Heat-shrinkable terminals, splices, disconnects

### Heat-shrinkable ring terminals & heat-shrinkable locking fork terminals




Heat-shrinkable ring terminals



Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
RAS18-6X	100	22-18	0.170	#6	ERG4255	1.23	0.25	0.27	1.10	0.03
RAS18-8X	100	22-18	0.170	#8		1.26	0.31	0.27	1.10	0.03
RAS18-10X	100	22-18	0.170	#10		1.26	0.31	0.27	1.10	0.03
RBS14-6X	100	16-14	0.200	#6		1.23	0.25	0.27	1.10	0.03
RBS14-8X	100	16-14	0.200	#8		1.23	0.25	0.27	1.10	0.03
RBS14-10X	100	16-14	0.200	#10		1.26	0.31	0.27	1.10	0.03
RCS10-6X	50	12-10	0.250	#6		1.34	0.31	0.27	1.15	0.04
RCS10-8X	50	12-10	0.250	#8		1.34	0.37	0.27	1.15	0.04
RCS10-10X	50	12-10	0.250	#10		1.34	0.37	0.27	1.15	0.04
RCS10-14X	50	12-10	0.250	¼		1.34	0.49	0.32	1.15	0.04

Diagram



Heat-shrinkable locking fork terminals



Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
RAS18-6FLX	100	22-18	0.170	#6	ERG4255	1.350	0.25	-	-	0.03
RAS18-8FLX	100	22-18	0.170	#8		1.350	0.29	-	-	0.03
RAS18-10FLX	100	22-18	0.170	#10		1.350	0.29	-	-	0.03
RBS14-6FLX	100	16-14	0.200	#6		1.350	0.25	-	-	0.03
RBS14-8FLX	100	16-14	0.200	#8		1.350	0.29	-	-	0.03
RBS14-10FLX	100	16-14	0.200	#10		1.350	0.29	-	-	0.03
RCS10-6FLX	50	12-10	0.250	#6		1.350	0.31	-	-	0.04
RCS10-8FLX	50	12-10	0.250	#8		1.350	0.37	-	-	0.04
RCS10-10FLX	50	12-10	0.250	#10		1.350	0.37	-	-	0.04
RCS10-14FLX	50	12-10	0.250	¼		1.350	0.49	-	-	0.04

Diagram

