



RECOMMENDED LAYOUT FOR .062 THICK P.C. BOARD

- PARTS COMPLY WITH TE SOLDERABILITY SPEC. NO. 109-11-3
- CONTACT IS PLATED OVERALL WITH .000050 NICKEL, THEN .000030 GOLD OVER CONTACT LENGTH INDICATED AND TIN PLATED ON SOLDER TAIL END.
- DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

SUPERSEDED BY 2-1586546-0

2-380999-0	NYLON	NATURAL	COPPER ALLOY GOLD
1-380999-0	NYLON -	NATURAL	COPPER ALLOY PRE-TIN
ASSEMBLY NO.	HSG. MATL.	COLOR	PIN MATL. FINISH

REVISION RECORD				NUMBER	REQUIRED PER ASSEMBLY	DWG. SIZE	NUMBER	NAME	REMARKS	ITEM NO.
DR	CHK	APP	DATE							
U4			REVIS PER ECR-21-117186	380999						
U3			REVIS PER ECR-18-008156							
U2			REVIS PER ECR-13-008342							
U1			REVIS PER ECO-11-005294							
LTR			REVISION RECORD							

  

DR	<i>P.J. Hoffmann</i> 3/20/73	MATERIAL AND FINISH	SEE TABLE		
CHK	<i>L.M. Peterson</i> 3/20/73	WIRE - RANGE - INSULATION		TYPE	PIN HEADER
DE	<i>Shubler</i> 4-3-73	TOLERANCE EXCEPT AS NOTED	± 1% 0'	LOC	CM
APP	<i>Shubler</i> 4-3-73	SCALE		NO	B 380999
		NAME	6 CIRCUIT MATE-N-LOK P.C. BOARD HEADER	P	U4

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.