



Part Number : [503948051](#)


Product Description : 2.00mm Pitch, Milli-Grid Female Crimp Terminal, 0.38µm Select Gold, Reel, Lead free

Series Number : 50394

Status : Active

Product Category : Crimp Terminals

Packaging Alternative : 503948100 (Bag)



---

## Documents & Resources

### Drawings

[503948051\\_sd.pdf](#)

[503940001-000.pdf](#)

### 3D Models and Design Files

[503948051\\_stp.zip](#)

### Specifications

[PS-51110-001-001.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Crimp Terminals
Series	50394
Description	2.00mm Pitch, Milli-Grid Female Crimp Terminal, 0.38µm Select Gold, Reel, Lead free
Application	Signal, Wire-to-Board, Wire-to-Wire
Product Name	Milli-Grid
UPC	800753576193

### Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	125V AC (RMS)/DC

### Physical

Durability (mating cycles max)	50
Gender	Female
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Nickel
Net Weight	43.000/mg
Packaging Type	Reel
Plating min - Mating	0.381µm
Plating min - Termination	2.000µm
Termination Interface Style	Crimp or Compression

Wire Insulation Diameter	1.40mm max.
Wire Size (AWG)	24, 26, 28, 30
Wire Size mm <sup>2</sup>	N/A

### Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

### Use with Part(s)

Description	Part Number
Milli-Grid Single Row Receptacle Housings	<u>151100</u>
Milli-Grid Dual Row Receptacle Housings	<u>151192</u>
Milli-Grid Dual Row Receptacle Housings	<u>51110</u>

### Application Tooling

#### Global

Description	Part Number
Hand Crimp Tool for Milli-Grid and MicroBlade Crimp Terminals, 30-24 AWG	<u>2133091200</u>
Extraction Tool for SPOX, MX64, Ditto, MX150CE, Milli-Grid Terminals	<u>638131400</u>
FineAdjust Applicator for 2.00mm Pitch Wire-to-Board Crimp Terminals, 30-24 AWG Wire, Insulation OD 1.10-1.30mm	<u>639005200</u>
FineAdjust Applicator for 2.00mm Pitch Wire-to-Board Crimp Terminal, 30-24 AWG, Insulation OD 0.90-1.10mm	<u>639046800</u>
T2 Terminator Die	<u>639105200</u>

### Application Tooling

#### Japan

Description	Part Number
-------------	-------------

S-1 Applicator for Milli-Grid Receptacle Terminal, 30-24 AWG	<u>573153700</u>
---	------------------

---

This document was generated on Apr 29, 2025